

High-efficiency Cellar Cooling **LITEAIR** SYSTEM



ECA Qualifying Cellar Coolers & Cool Storage Systems

LC/LE INSTALLATION MANUAL



Authorised User No. 00460



Choice of 4 condensing units

- **2.7KW - 6.5KW**

Choice of 4 stainless steel evaporators

- **Electronic [E] or Mechanical [M]**
- **Optional factory fitted heater**

The Hubbard LITEAIR ECA Qualifying system is designed to energy-efficiently chill cellars and perishable goods storage areas.

Suitable for a wide range of products it is ideal for the storage of barreled beers and bottled beverages.

Designed for quietness the condensing unit (LC) is housed in a self-healing smart steel case for internal or external mounting. The evaporator (LE) can be wall or roof

mounted and contains the system's temperature controller.

A heating option is available where conditioning is required for the correct storage of cask conditioned ales.

The Range*

The Hubbard LITEAIR range comprises of four models. R410a refrigerant provides cooling capacities from 2.7 kW to 6.5 kW. These systems are supplied as standard for single phase operation with connection to either internal or external units.

* Cellar temperature from 12.7°C to 5°C DB, ambient 27°C.



Condensing Unit (LC)

The Hubbard LITEAIR unit is designed for external placement and is finished in a light grey Plastisol 'self-healing' smart steel for long service. It can be floor or wall mounted.

Its slim design makes it ideal for situations where space is limited and this also reduces the visual impact of the installation. The access panels are easily removable for service of the main components. Including the compressor, condenser coil complete with fan for quiet operation, HP and LP safety switch HP fan control switch and compressor starter gear.



Evaporator Unit (LE)

The Hubbard LITEAIR evaporator consists of a stainless steel cased enclosure which can be ceiling mounted as standard, or wall mounted.

Evaporators are supplied ready assembled with an expansion valve device, and an electric controller (mechanical option) which operates the compressor directly through an interconnecting control loop. The LITEAIR requires a 4 core (including earth) interconnecting cable. The cable size is dependent on whether the supply is bought to the evaporator or condensing unit.

Condensing unit Features:

- Fuse Protection
- Rotary compressor
- Condenser fan
- HP/LP pre-sets
- HP condenser fan control switch

Evaporator Section Features:


- Fused component protection
- Expansion device for refrigerant control
- Mechanical or electronic control

System options:

- Factory fitted electric heater


Condenser model Dimensions (mm)

|  | width (A) | height (B) | depth (C) | weight (kg) |
|--|-----------|------------|-----------|-------------|
| LC75 | 720 | 610 | 250 | 42 |
| LC100 | 720 | 610 | 250 | 42 |
| LC150 | 800 | 765 | 320 | 60 |
| LC200 | 800 | 765 | 320 | 64 |



Evaporator Dimensions (mm)

|  | width (A) | height (B) | depth (C) | weight (kg) |
|--|-----------|------------|-----------|-------------|
| LE75 | 805 | 450 | 475 | 25 |
| LE100 | 805 | 450 | 475 | 27 |
| LE150 | 805 | 450 | 475 | 27 |
| LE200 | 865 | 525 | 525 | 40 |



INSTALLATION GUIDE

LC LITEAIR Condensing Unit

Location

The Hubbard LITEAIR LC unit can either be mounted on a level surface or suspended from a vertical wall.

The unit should always be mounted on a load bearing wall and NOT a partition wall.

The sides should have a minimum clearance from obstruction of 600mm and the minimum clearance for the front of the machine should be 1.0 metres. The minimum clearance for the rear of the machine should be 130mm.

Fixing

Two-off hole fixings and two-off slot fixings suitable for M10 fixings are provided in the base of the unit to secure the unit to a suitable plinth, or to wall mount brackets.

If required, the contractor should install the unit on anti-vibration pads.

Service connections

The refrigerant pipe and electrical connections are located at the right hand end of the unit. Ensure there is adequate air entry at the back of the unit.

NB

ENSURE THE CONDENSER HAS ADEQUATE CLEARANCE AROUND IT AND IS NOT AFFECTED BY NEIGHBOURING CONDENSING UNITS AND OTHER OBSTRUCTIONS.

LE LITEAIR Evaporator Unit

Location

The Hubbard LITEAIR LE unit should be mounted level on a load bearing wall or ceiling. The minimum distance from the floor should be 1.8 metres to ensure good air convection.

The sides should have a minimum clearance from obstruction of 100mm and the minimum clearance for the front of the machine should be 1.5 metres.

Fixing

The unit should be fixed to the wall using two-off rear fixings or to the ceiling using the two-off top fixings. 10mm Rawl Bolts with large steel washers are recommended for fixing to a local load bearing wall or ceiling. Locking screw holes to be used to prevent equipment moving once installed.

Service connections

The refrigerant pipe connections are accessed through the left hand side panel.

Cable entry is on the right hand side of the unit. A plastic drain connector is supplied to be site fitted onto the condensate tray.



Capacities R410a

| LITEAIR Model | Supply | Total cooling duty 12.7°C db 10°C wb internal | | Total cooling duty 5°C db (1) 3.5°C wb internal | | Recommended line sizes for max 20m run* | |
|----------------|--------|---|--------|---|--------|---|--------|
| | | kW | Btu/hr | kW | Btu/hr | Suction | Liquid |
| LC75 LE75 | 1PH | 2.7 | 9212 | 2.1 | 7165 | 1/2" | 1/4" |
| LC100 LE100 | 1PH | 3.4 | 11601 | 2.7 | 9212 | 5/8" | 1/4" |
| LC150 LE150 | 1PH | 5.1 | 17401 | 4.0 | 13648 | 5/8" | 3/8" |
| LC200 LE200 | 1PH | 6.5 | 22178 | 5.1 | 17401 | 3/4" | 3/8" |

(1) For operating temperatures below 8°C use Electronic Controller only (Not Electro mechanical control option).

Technical data LC condensing Units:

| LC Model | Refrigerant Connections | | Condenser Fans | | Size Reference | Weight kg (dry) | Noise Levels Free field | |
|-----------|-------------------------|--------|----------------|---------------------|----------------|----------------------|-------------------------|---------------|
| | Suction | Liquid | No. | m ³ /s | | | @2m - internal | @3m -external |
| LC75 | 1/2" | 1/4" | 1 | 0.54 | 1 | 42 | 61 | |
| LC100 | 5/8" | 1/4" | 1 | 0.45 | 1 | 42 | 48 | |
| LC150 | 5/8" | 3/8" | 1 | 0.45 | 2 | 60 | 47 | |
| LC200 | 3/4" | 3/8" | 1 | 0.95 | 2 | 64 | 53 | |
| LC Model | Case dimensions mm | | | Mounting centres mm | | Airflow clearance mm | | |
| | Width | Height | Depth | Width | Slot size | Sides | Back | Front |
| LC75/100 | 720 | 610 | 250 | 570 | 240 | 600 | 130 | 1000 |
| LC150/200 | 800 | 765 | 320 | 620 | 310 | 600 | 130 | 1000 |

Technical data LE evaporating Units:

| LE Model | Connections | | Evaporator fans | | Air Throw m | Weight kg (dry) | Drain connection | Heating Cap kW | |
|------------|--------------------|--------|-----------------|---------------------|-------------|-----------------------|----------------------|----------------|-------|
| | Suction | Liquid | No. | Diameter mm | | | | | |
| 75 | 1/2" | 1/4" | 1 | 350 | 7.5m | 25 | 3/4" BSP | 1.5 | |
| 100 | 5/8" | 1/4" | 1 | 350 | 12m | 27 | 3/4" BSP | 1.5 | |
| 150 | 5/8" | 3/8" | 1 | 350 | 12m | 27 | 3/4" BSP | 1.5 | |
| 200 | 3/4" | 3/8" | 1 | 400 | 13.5m | 40 | 3/4" BSP | 1.5 | |
| LE Model | Case dimensions mm | | | Mounting centres mm | | | Airflow clearance mm | | |
| | Width | Height | Depth | Width | Depth | Slot size | Sides | Floor | Front |
| 75/100/150 | 805 | 450 | 475 | 618 618 | - 210 | 10 Wall 10 Ceiling | 100 | 1800 | 1500 |
| 200 | 865 | 525 | 525 | 678 | 201 | 10 | 100 | 1800 | 1500 |

Electrical data:

| LITEAIR R410a | Supply required | Compr. FLA | Condenser Fan(s) | Evaporator Fan(s) FLA | Total Cooling FLA | HRE Fuse FLA | Mains supply cores to conduit | Total no. of interconnecting cables |
|---------------|-----------------|------------|------------------|-----------------------|-------------------|--------------|-------------------------------|-------------------------------------|
| 75 | 1 ph | 4.0 | 0.35 | 0.52 | 4.87 | 10A | 3 core | 4 core |
| 100 | 1 ph | 5.5 | 0.35 | 0.73 | 6.58 | 10A | 3 core | 4 core |
| 150 | 1 ph | 8.6 | 0.35 | 0.73 | 9.68 | 16A | 3 core | 4 core |
| 200 | 1 ph | 10.4 | 0.65 | 0.73 | 11.75 | 20A | 3 core | 4 core |

LC/LE System Installation

Table 7 - General service connections




Table 7.1 - Unit connections and interconnections

| | |
|-----------------------------|---------------------|
| 7.1 - Liquid connections | See tables overleaf |
| 7.2 - Suction connections | |
| 7.4 - Condensing unit | |
| 7.5 - Interconnecting cable | |
| 7.7 - Power cable | |
| 7.8 - Isolator/fuses | Supplied by others |

SPECIAL NOTES

CHECK LOCAL REGULATIONS FOR INDOOR/OUTDOOR ELECTRICAL ISOLATION REQUIREMENTS AND REFRIGERATION PIPEWORK STANDARDS

LC/LE System Installation

General service connections and interconnections

Table 7.3 - ICC Refrigerant connections

| | LC/LE 50 | LC/LE100 | LC/LE150 | LC/LE200 |
|---------------------|----------|----------|----------|----------|
| Liquid connections | 1/4" | 1/4" | 3/8" | 3/8" |
| Suction connections | 1/2" | 5/8" | 5/8" | 3/4" |

Table 7.4 - ICU Refrigerant connections

| | LC/LE 50 | LC/LE100 | LC/LE150 | LC/LE200 |
|---------------------|----------|----------|----------|----------|
| Liquid connections | 1/4" | 1/4" | 3/8" | 3/8" |
| Suction connections | 5/8" | 5/8" | 5/8" | 3/4" |

Table 7.5 - Interconnecting cable - No. of cores

| | LC/LE 50 | LC/LE100 | LC/LE150 | LC/LE200 |
|--------------------|----------|----------|----------|----------|
| A/C Unit | 4 | 4 | 4 | 4 |
| A/C Unit + Heaters | 4 | 4 | 4 | 4 |

Table 7.7 - Mains power cable - No. of cores

| | LC/LE 50 | LC/LE100 | LC/LE150 | LC/LE200 |
|--|----------|----------|----------|----------|
| Single phase system 230/240 V 50 Hz | 3 | 3 | 3 | 3 |
| Single phase system 230/240 V 50 Hz | N/A | N/A | N/A | N/A |


Table 7.8 - System fuse ratings - HRC

| | LC/LE 50 | LC/LE100 | LC/LE150 | LC/LE200 |
|--------------------|----------|----------|----------|----------|
| A/C Unit | 10 | 10 | 16 | 20 |
| A/C Unit + Heaters | 16 | 16 | 16 | 20 |

LC/LE System Installation

Table 8 - power and control connections

figure 8.1 - electrical interconnecting diagram



8.1 - Wiring-up the unit

Electrical terminations should be made onto the screw terminal side of the indoor and outdoor unit terminal blocks.

8.2 - Wiring requirements

Power supply - Connection of isolation power supply to the outdoor unit.

Interconnecting wiring - Power and signal cables run between the outdoor and indoor unit.

Details of the fuse ratings and cable requirements are given in tables 7.5, 7.7 and 7.8 of this manual

8.3 - Terminations

Details of terminations and interconnections are given in figure 8.1



SPECIAL NOTES

DO NOT MEGGER OR FLASH TEST WITH ELECTRIC PCB'S IN CIRCUIT !!

INDOOR AND OUTDOOR UNITS SHOULD HAVE LOCAL ELECTRICAL ISOLATORS



Refrigeration commissioning



Evacuation, Charging and Refrigerant Procedures

After completing the refrigerant connections the following steps should be followed with reference to the above.

1. Service gauges - Connect the low pressure port (1) of a manifold gauge set to the suction line outdoor unit shut-off valve service port (2). Open both the outside unit service shut-off valves (7 & 8).
2. Vacuum pump - Connect the centre line port (3) of the manifold gauge set to the vacuum pump (4) and operate the pump to ensure a vacuum of 200 microns.
Note: Ensure gauge low-pressure port (5) is open and high-pressure port (6) is closed.
3. System isolation - After achieving the specified system vacuum, close the gauge low-pressure port (5) and switch off the vacuum pump. Leave the system for one hour and check that the vacuum is maintained. If not, check for leaks, rectify and repeat the pumping down to 200 microns.
4. Refrigerant charging - Weigh in the charge using a charging station and any additional extended pipe run charge as detailed below.
5. Disconnect the vacuum pump and connect the gauge high-pressure port (9) to the discharge line of the outdoor unit shut-off valve (10), ensuring the gauge central port (3) is closed. Run the system, allow pressures to stabilise and ensure correct operation. After final commissioning remove the gauge set, fit all the valve caps and carry out the final refrigerant leak test.

Refrigeration commissioning

System charge weights

| R410a | LC75 | LC100 | LC150 | LC200 |
|--------------------|---------|---------|---------|---------|
| Site Base Charge | 1450gms | 1850gms | 2050gms | 2650gms |
| Top up charge/m>5m | 25g | 25g | 40g | 40g |

Horizontal or Downflow application (suction line)

| Table A | | 5 | 10 | 15 | 20 | 25 |
|---------|---------|------|------|------|------|------|
| LC75 | Suction | 3/8" | 1/2" | 1/2" | 1/2" | 1/2" |
| | Liquid | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" |
| LC100 | Suction | 1/2" | 1/2" | 1/2" | 5/8" | 5/8" |
| | Liquid | 1/4" | 1/4" | 1/4" | 1/4" | 1/4" |
| LC150 | Suction | 1/2" | 1/2" | 1/2" | 5/8" | 5/8" |
| | Liquid | 3/8" | 3/8" | 3/8" | 3/8" | 3/8" |
| LC200 | Suction | 5/8" | 5/8" | 3/4" | 3/4" | 3/4" |
| | Liquid | 3/8" | 3/8" | 3/8" | 3/8" | 1/2" |

Upflow application (suction line)

| Table B | | Max. Size | Max. Lift | R410Ac - kg additional charge |
|---------|---------|-----------|-----------|-------------------------------|
| LC75 | Suction | 3/8" | 5 | >5m = 25g/m (1/4" Liquid) |
| LC100 | Suction | 1/2" | 5 | >5m = 25g/m (1/4" Liquid) |
| LC150 | Suction | 1/2" | 5 | >5m = 40g/m (3/8" Liquid) |
| LC200 | Suction | 3/4" | 5 | >5m = 40g/m (3/8" Liquid) |

Technical helpline 01473 892280

We reserve the right to change specifications without notice. Details correct at time of going to press.

Hubbard Products Ltd, 1-7 Bluestem Rd., Ipswich, Suffolk IP3 9RR

Tel: 01473 892289 Fax: 01473 711799

Email; commercial@hubbardproducts.com

www.hubbardproducts.com